

BELKIN 2.4A FULL RATE USB CHARGERS

Convenient charging for your mobile devices.



Recharge multiple devices simultaneously with the Belkin 4-Port and 10-Port 2.4A Full Rate USB Chargers.

Today's mobile professionals depend on their mobile devices for instant access to information and resources, whether they're at home, in the office, or out in the field. Tech-savvy individuals frequently use multiple devices, including tablets, smartphones, and various accessories. Keeping them all charged and ready for action can be a hassle.

Belkin 4-Port and 10-Port 2.4A Full Rate USB Chargers make professional mobility more practical and convenient. No more searching for available USB ports or wall-plug adapters, no more swapping devices, no more second-guessing battery levels and charging times. One charger offers four or even ten dedicated, powered USB ports, allowing you to recharge multiple devices at once, all in the same place. The sleek, modern design fits neatly into any desktop, conference room, or home office environment. Simplify your mobility with a Belkin USB Charger.

Key Features and Benefits

- Hot-plug, auto-sense detection for up to 2.4A full rate charge per device
- Charges up to 14% faster than traditional 2.1A USB chargers
- Backward compatible to USB 2.0
- Ideal for home or office
- FCC/CE/UL rated

Convenient charging for your mobile devices.

BELKIN USB CHARGERS



Specifications

Safety

Approval status	FCC/CE/UL
-----------------	-----------

Overviews

Outlet (total)	4 or 10 ports
----------------	---------------

Color	White/Gray
-------	------------

Housing	Plastic
---------	---------

Power

Electrical rating	10A / 250V AC / 60Hz / 2,500W
-------------------	-------------------------------

Auto shut down	Yes
----------------	-----

AC plug type	U.S. and worldwide regions available
--------------	--------------------------------------

Cord length	1.5 m (1.0 mm ²)
-------------	------------------------------

Maximum handling current	10A
--------------------------	-----

Surge suppression

Surge energy Joule rating (total)	306J
-----------------------------------	------

L-N mov	14D471S1
---------	----------

EM1/RF1 noise filter

Attenuation (dB)	20 dB
------------------	-------

Indicator light

Protected LED indicator	Green
-------------------------	-------

Grounded	Green
----------	-------

USB charger

Number of ports	4 or 10 ports
-----------------	---------------

Output	5V / 2.4A for 4 and 10 ports
--------	------------------------------

Output range	4.75V DC ~ 5.25V DC
--------------	---------------------

Overcurrent protection	< 2.7A
------------------------	--------

Output ripple current	< 150mV p-p
-----------------------	-------------